



Model name		ADTD15PN01.0
Panel	Model	G156HTN02.0
	Resolution	1920 x 1080
	Size	15.6 inch
	Display Area	344.16 (H) x 193.59 (V) mm
	Brightness	340 cd/m ² (Typ.), 270 cd/m ² (Min.) After Touch
	Contrast	700 : 1 (Typ.), 500 : 1 (Min.)
	View Angle	80°/ 80°/ 70°/ 70° (L/R/U/D, Typ.)
	Response Time	8 ms (Rising + Falling, Typ.)
	Color	16.7M Colors (RGB 8-bits)
	Aspect Ratio	16:9
	LED Backlight Lifetime	50,000 hrs. (Typ.), 30,000 hrs. (Min.)
	Display Orientation	Landscape
Touch Panel	Touch Type	Projected Capacitive Touch
	Structure	G/G Type, 3mm (Cover Glass)
	Controller IC	ILI2510
	Interface	USB
	Multi-touch	10 Points
	Transmission Rate	≥ 85%
	Bonding	Air Bonding
	Surface Hardness	≥ 6 H
Power	Consumption	< 20 W
	Input	DC12V, 5A
Environment	Operating Temp.	0 ~ 50 °C
	Operating Humidity	5 ~ 90% RH
	Storage Temp.	-20 ~ 60 °C
	Storage Humidity	5 ~ 90% RH
Dimensions	Body Size	367.3 (H) x 222.1 (V) x 43 (D) mm
	Package Size/ Carton	450 (H) x 640 (V) x 160 (D) mm
	Net Weight	2.8 kg
	Monitor with Stand Size	4.1 kg
Other	Operation	OSD Menu, Multi-Language
	Accessory	AC/DC Adapter*1, Power Cord*1, USB-A Cable*1
	Speaker	N/A (Optional)
	I/O ports	VGA*1, DVI*1, HDMI*1, Audio-in*1, USB-A*1 for touch, DC IN
	Wall Mounting	VESA (75 x 75mm / 100 x 100mm, 4-M4*6mm Depth)
Optional	Light sensor	
Application	Digital Signage / Kiosk etc.	

Note: Specifications are subject to change without notice.